

General	
Panel Type	0.63" LCD x 3
Lamp	240W x 1
Brightness	4500 lumens
Lens	F1.60-1.90, f15.31-26.24mm
Contrast (Full on / Full off)	20000:1
Resolution (Native / maximum)	XGA
Video Compatibility	PAL, PAL-M, PAL-N, PAL60, SECAM, NTSC, NTSC4.43
Screen Size	30" - 300"
Keystone Correction Range	Vertical $\pm 35^\circ$ ( $\pm 30^\circ$ when Auto); Horizontal $\pm 35^\circ$
Weight	Approx 3.3kg
Dimensions (W x H x D)	352 x 98 x 279.4 mm
Power Consumption	320W (Standby mode : 8.0W, 0.5W(eco), 1.0W(network))
Terminals	HDMI (19 pin x 1) PC1 in (D-sub HD 15-pin x 1) PC2 in/Monitor out (D-sub HD 15-pin x 1) Video in (Pin jack x 1) Audio in 1 (M3 Stereo Mini Jack x 1) Audio in 2 (M3 Stereo Mini Jack x 1) Audio in 3 (Pin jack x 2) Audio out (M3 Stereo Mini Jack x 1) LAN (RJ45 x 1) Serial in (D-sub 9 pin x 1) USB A (USB Type a for memory viewer / wireless module) USB B (USB Type B (for USB Display) x 1)
Replacement Lamp	ET-LAV300
Optional Accessories	ET-PKL100H (High ceiling mount bracket) ET-PKL100S (low ceiling mount bracket) ET-PKL400B(mount bracket) ET-RFV300(filter unit)
Optional Lens	--
Standard Accessories	Wireless remote control unit Battery for remote control unit Power cord VGA cable Lens cap