

General	
Panel Type	0.64" LCD x 3
Lamp	NA (Laser diodes)
Brightness	5000 lumens
Lens	F1.60-2.12, f15.30-24.64mm
Contrast (Full on / Full off)	3,000,000:1
Resolution (Native / maximum)	WUXGA
Video Compatibility	PAL, PAL-M, PAL-N, PAL60, "PAL, PAL-M, PAL-N, PAL60, SECAM, NTSC, NTSC4.43
Screen Size	30" - 300"
Lens Shift	Vertical +44°; horizontal +20°
Keystone Correction Range	Vertical ±25°; horizontal ±35°
Weight	Approx 7.2kg
Dimensions (W x H x D)	399 x 115 x 348 mm
Power Consumption	370W
Terminals	HDMI (19-pin x 2) PC1 (D-sub 15-pin x 1) PC2 in/mon out (D-sub 15-pin x 1) Video (Pin jack x 1) Audio 1(M3 stereo mini jack (L/R x 1) Audio 2(M3 stereo mini jack x1/mic in) Audio 3(Pin jack (L/R) x 1) Audio out (M3 stereo mini jack x 1) Serial (D-sub 9-pin x 1) LAN (RJ-45 x 1, 10Base-T/10/100Base-TX) Digital Link/LAN (RJ-45 x1) USB(Viewer/Wireless/DC out)
Optional Accessories	ET-RFV500 (Replacement filter unit)AJ-WM50 (Wireless module)
Optional Lens	--
Standard Accessories	Lens cap RGB cable Power cord Battery for remote control unit Wireless remote control unit