

EB-1975W

DATASHEET



The EB-1975W is a well-connected business projector, benefiting from a high brightness of 5,000 lumens and WXGA resolution. Epson's 3LCD technology provides high White and Colour Light Output for bright images and vivid colours, while Miracast and WiDi allow wireless screen-mirroring and easy streaming from a tablet or smartphone.

High quality

Professional environments are treated to presentations in more detail than ever before thanks to the EB-1975W's WXGA resolution, which fits the resolution and aspect ratio of most laptops. That detail shines through, even in daylight, thanks to 5,000 lumens brightness.

More vivid colours

Epson's own 3LCD technology ensures high-quality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than leading competitive projectors¹.

Easy to set up

Focus help, keystone correction and screen fit modes are included to ensure that set-up is simple, while flexible connectivity options include two HDMI ports, Wi-Fi and wired LAN.

Share content

With Miracast and WiDi, the EB-1975W can easily stream content from, and mirror the screen of, a range of smart devices, and is compatible with Epson's iProjection app². Content, such as a multi-source video conference and presentations, can be displayed in split-screen, while Multi-PC Projection software supports up to 50 PCs for collaboration in large meetings.

Built-in speakers

Epson recognises that video is being used more often within presentations, so as well as a high-resolution image, this business projector also includes built-in 16W speakers.

KEY FEATURES

- **Ultra-bright images**
5,000 lumens White and Colour Light Output
- **Picture quality**
3LCD technology for vivid colours
- **High connectivity**
Benefit from Miracast, Wi-Fi connectivity and HDMI inputs
- **Focus help**
Easy-to-use focus pattern
- **Split-screen**
See content, like presentations and video conferences, simultaneously



EPSON
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.76 inch
IMAGE	
Colour Light Output	5,000 lumen-3,500 lumen (economy) In accordance with IDMS15.4
White Light Output	5,000 lumen - 3,500 lumen (economy) In accordance with ISO 21118:2012
Resolution	WXGA, 1280 x 800, 16:10
Contrast Ratio	10,000 : 1
Lamp	280 W, 200 W (economy mode), 3,000 h durability, 4,000 h durability (economy mode)
Keystone Correction	Auto vertical: $\pm 30^\circ$, Auto horizontal $\pm 30^\circ$
Aspect Ratio	16:10
OPTICAL	
Projection Ratio	1.38 - 2.28:1
Zoom	Manual, Factor: 1 - 1.6
Projection Size	30 inches - 300 inches
Projection Distance Wide	0.9 m - 9 m
Projection Distance Tele	1.5 m - 14.8 m
Focal Distance	23 mm - 38.4 mm
Focus	Manual
Offset	10 : 1
CONNECTIVITY	
Interfaces	USB 1.1 Type A, RS-232C, Wireless LAN IEEE 802.11b/g/n, VGA in (2x), VGA out, HDMI in (2x), Composite in, Component in, MHL, Stereo mini jack audio out, Stereo mini jack audio in (2x), Ethernet interface (100 Base-TX / 10 Base-T)
ADVANCED FEATURES	
Security	Kensington lock, Security cable hole, Wireless LAN unit lock
Features	Automatic keystone correction, Built-in speaker, Screen Fit, PC Free, Quick Corner, Split-Screen-Function
Video Colour Modes	Blackboard, Dynamic, Photo, Presentation, sRGB, Theatre, Whiteboard, DICOM SIM
GENERAL	
Energy Use	411 W, 316 W (economy), 3.5 W (standby)
Product dimensions	377 x 292 x 125 mm (Width x Depth x Height)
Product weight	4.6 kg
Noise Level	Normal: 39 dB (A) - Economy: 32 dB (A)
Included Software	EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection
Loudspeaker	16 W
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Temperature	Operation 5° C - 35° C, Storage -10° C - 60° C
Humidity	Operation 20% - 80%, Storage 10% - 90%
Options	Document camera, Quick wireless USB key, Soft carry case
OTHER	
Warranty	36 months On site service or 8,000 h, Lamp: 12 months or 1,000 h Optional warranty extension available

EB-1975W

WHAT'S IN THE BOX

- CD Manual
- Computer cable
- Power cable
- Remote control incl. batteries
- User manual
- Wireless LAN unit

1. - Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour Brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour Brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO2-iProjection App available on Android and iOS devices

EPSON[®]

OPTIONAL ACCESSORIES

- Lamp - ELPLP77
V13H010L77
- Quick Wireless Connect USB key - ELPAP09
V12H005M09
- Air Filter - ELPAF41
V13H134A41
- Soft Carry Case - ELPKS68
V12H001K68
- Ceiling Mount (White) - ELPMB23
V12H003B23
- Ceiling Pipe (450mm) - ELPPF13
V12H003P13
- Ceiling Pipe (700mm) - ELPPF14
V12H003P14
- Control and Connection Box - ELPCB02
V12H614040DA

LOGISTICS INFORMATION

SKU	V11H621041
EAN code	8715946538662
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	40 Units
Pallet Size Block	50 Units

For more information please contact:

Telephone: 01952 607111 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740
+ Local call rate.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON[®]