

## Display

<b>Aspect Ratio</b>	16x9	<b>Native Resolution</b>	1080p 1920x1080
<b>Maximum Resolution</b>	WUXGA 1920 x 1200	<b>Contrast Ratio (typical)</b>	10,000:1 with auto iris

## Synchronization Range

<b>Horizontal (Analog/Digital)</b>	15-100 kHz	<b>Vertical</b>	50-120 Hz
------------------------------------	------------	-----------------	-----------

## Signal Compatibility/Connectivity

<b>Supported Video Standards</b>	NTSC, NTSC 4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM	<b>SD/HD Video Signal Compatibility</b>	Y/CB/Cr component (with optional adaptor ADP-CV1E) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
<b>PC Signal Compatibility</b>	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA	<b>Macintosh Signal Compatibility</b>	Yes
<b>Sync Compatibility</b>	Separate Sync / Composite Sync / Sync on G	<b>External Control</b>	RS-232, IR, Wired LAN, DDC/CI, USB, Wireless LAN (optional)

### Input Terminals

RGB1(analog):  
VGA 15-pin D-sub  
RGB3(digital):  
HDMI w/ HDCP  
RGB4(digital):  
HDMI w/ HDCP  
RGB5(digital):  
USB A type  
Video 1:  
RCA  
Audio 1:  
L/R RCA (shared by video sources)  
Audio 2:  
1/8 in. stereo  
Audio 3:  
Microphone

### Output Terminals

Audioout:  
Yes (variable)  
Monitor Out:  
VGA 15-pin D-sub

## Power Consumption (typical)

<b>On</b>	336W / 221W / 2.5W / 0.2W	<b>Input Current</b>	3.9A/1.2A
<b>Power Requirements</b>	100-240V AC, 50/60 Hz		

## Physical Specifications

---

**Dimensions (WxHxD)**

Product:

14.5 x 11.5 x 4.3 in. / 368 x 292 x 108mm

**Weight**

Net Weight:

7.7 lbs. / 3.5 kg

---

**Environmental Conditions****Operating Temperature** 41-104°F / 5-40°C**Storage** -14-122°F / -10-50°C

---

**Limited Warranty (parts & labor)**

Registered owners receive a 3 year parts and labor warranty including InstaCare next business day exchange. One year on lamp.