Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.62 inch with C2 Fine
Image	
Color Light Output	4,500 Lumen- 3,150 Lumen (economy) In accordance with IDMS15.4
White Light Output	4,500 Lumen - 3,150 Lumen (economy) In accordance with ISO 21118:2012
Resolution	Full HD 1080p, 1920 x 1080, 16:9
High Definition	Full HD
Aspect Ratio	16:9
Contrast Ratio	2,500,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Auto vertical: ± 30 °, Manual horizontal ± 30 °
Colour Video Processing	10 Bits
2D Vertical Refresh Rate	192 Hz - 240 Hz
Colour Reproduction	Upto 1.07 billion colours

Optical

Throw Ratio 1.33 - 2.16:1

Zoom Manual, Factor: 1 - 1.62

Projection Lens Zoom Ratio	1.33 - 2.16 : 1
Lens	Optical
Screen Size	40 inches - 500 inches
Projection Lens F Number	1.49 - 1.77
Projection Lens Focal Length	18.2 mm - 29.2 mm
Projection Lens Focus	Manual
Offset	10 : 1

Connectivity

USB Display Function	3 in 1: Image / Mouse / Sound
Interfaces	USB 2.0 Type A, USB 2.0 Type B, RS-232C, Wired Network, Wi-Fi Direct, VGA in (2x), VGA out, Composite in, Miracast, Stereo mini jack audio out, Stereo mini jack audio in (2x), Cinch audio in, Microphone input, HDMI (HDCP 2.2) (2x), Wireless LAN IEEE 802.11a/b/g/n/ac
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	PJLink

Advanced Features

Security	Kensington lock, Padlock, Security cable hole, Wireless LAN unit lock
2D Colour Modes	Dynamic, Cinema, Presentation, sRGB, Game
Other features	AV Mute Slide, Auto source search, Built-in speaker, Customizable user logo, Document Camera Compatible, Home Screen, Instant on/off, Long light source life, OSD copy function, PC Free, Quick Corner, Screen Mirroring, Screen share, Split-Screen-Function, Wireless LAN capable, iProjection App, iProjecton set-up by QR code

Video Color Modes	Cinema, Dynamic, Presentation, sRGB, DICOM SIM
Projector control	via: AMX, Crestron, Control4, Extron IP Link

General

Power consumption	254 Watt, 193 Watt (economy), 0.5 Watt (standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	325 x 299 x 90 mm (Width x Depth x Height)
Product weight	4.1 kg
Noise Level	Normal: 37 dB (A) - Economy: 28 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
Included Software	iProjection
Options	Connection and control box, Document camera, External Speaker, Soft carry case
Loudspeaker	16 Watt
What's in the box	Main unit, Power cable, Remote control incl. batteries
Room Type / Application	Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom
Positioning	Ceiling Mounted, Desktop
Colour	White
TCO Certified	Yes