

All Specifications

Display

Projection System	DLP Single 0.65" WXGA
Resolution	1280 x 800 pixels
Brightness (ANSI lumens)	4000 ANSI Lumens
Contrast Ratio (FOFO)	20000:1
Display Color	30 Bits (1,07 billion colors)
Native Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Light Source	Lamp
Light Source life*	Normal 6000 hr Economic 10000 hr SmartEco 10000 hr LampSave 15000hr
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)

Optical

Throw Ratio	1.55~1.7 (87" ±3% @ 2.9m)
Zoom Ratio	1.1X
Lens shift	NA
Projection Offset**	100%±2.5% (Full-Height)
Projection Size	60"~150"
Keystone Correction	Auto ID, Vertical +/- 40 degrees

Audio

Speaker	10W x 1
---------	---------

Special Feature

Security	Security Bar, Kensington lock
Feature	ID Auto Keystone, High Brightness, Spreadsheet mode, Bright Mode, Presentation Mode, Infographic Mode, Video Mode, Srgb Mode

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23 ~ 120 Hz
HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM, SDTV (480i/576i), EDTV (480p/576p), HDTV (720p, 1080i/p 60Hz)

Connectivity

HDMI	HDMI-1 x1 HDMI-2 x1
PC (D-sub 15pin)	x1
Monitor out (D-sub 15pin,Female)	x1
Audio in (mini jack)	x1
Audio out (mini jack)	x1
RS232 In (D-sub 9pin, male)	x1
USB TypeA-1	x1 (1.5A power)
USB Type mini B	x1
IR Receiver (Front+Top)	x2
S-Video	x1
Composite Video (RCA)	x1

Power

Power Consumption(Max/Normal/Eco)	Max 280W, Normal 260W, Eco 215W
Standby Power Consumption	Normal < 0.5Watts.

Power Supply 100 ~ 240V AC

Dimension and Weight

Net Weight (Kg/ lbs) 2.3kg +/- 200g

Dimensions (W x H x D)(mm) 296 x 120 x 221 mm

Operation Condition

Noise Level(Normal/Eco) 34 /29 dBA

Operating Temperature 0~40°C

Accessories (Standard)

Remote Control w/ Battery x 1 (5J.JND06.001)

Power Cord x 1 (1.8m)

Warranty Card (by region) x 1

VGA Cable x 1 (1.5m)

AAA Battery x2

QSG x1 (4J.JND01.001)

Accessories (Optional)

Spare Lamp Kit x 1 (5J.JND05.001)

Universal Ceiling Mount x 1

3D Glasses x 1 (5J.J9H25.002)

QCast Mirror dongle x 1 (5A.JH328.10X)

OSD

OSD Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/
Dutch/ English/ Finnish/ French/ German/ Greek/
Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/
Korean/ Norwegian/ Polish/ Portuguese/

Romanian/ Russian/ Simplified Chinese/Spanish/
Swedish/ Turkish/ Thai/ Traditional Chinese/
Farsi / Vietnamese/ (30 Languages)