

<b>Brightness</b>	4,500 ANSI Lumens
<b>Resolution</b>	1280x800
<b>Aspect Ratio</b>	16:10 (WXGA)
<b>Contrast</b>	6,000:1 (full on/off)
<b>Dynamic Iris</b>	Yes
<b>Display Type</b>	2 cm DLP x 1
<b>Color Processing</b>	8-bit
<b>Video Modes</b>	720p, 1080i, 1080p/60, 576i, 576p, 480p, 480i
<b>Data Modes</b>	MAX 1920x1200
<b>Lamp Type</b>	335W AC bulb
<b>Lamp Model</b>	NP38LP <a href="#">Buy Replacement Lamp</a>
<b>Included Lens</b>	1.7x manual zoom , manual focus
<b>Optional Lenses</b>	No
<b>Lens Shift</b>	Horizontal +/-28% & Vertical +59%
<b>Throw Distance</b>	1.4 m - 8.4 m <a href="#">Calculate Throw Distance</a>
<b>Image Size</b>	74 cm - 763 cm
<b>Throw Ratio</b>	1.30:1 - 2.20:1 (D:W)
<b>Projector Placement</b>	For a <input type="text" value="254"/> cm diagonal screen, place the projector lens between 2.8 m and 4.7 m from the screen.
<b>Digital Zoom</b>	Yes
<b>Digital Keystone</b>	Horizontal & Vertical

<b>Projector Size</b>	14 cm x 36 cm x 31 cm (HxWxD)
<b>Weight</b>	5.2 kg
<b>Audible Noise</b>	39 dB / 31 dB (Eco)
<b>Internal Speakers</b>	20.0 Watts Mono
<b>Power</b>	426 Watts 100V - 240V
<b>Connection Panel</b>	Audio In: Mini Jack Audio In: RCA Audio Out: Mini Jack Composite: RCA HDBaseT: RJ-45 HDMI x 2 Network: RJ-45 RS232: DB-9pin USB VGA In: Dsub-15pin VGA Out: Dsub-15pin
<b>Features</b>	Closed Captioning Geometric Correction Blackboard Mode Crestron RoomView™
<b>Additional Features</b>	IEU Lite (Image Express Utility Lite) for audio and video transmission from a computer to the projector over the network