

## Image Display

---

Display System	DLP
On-Screen Resolution	Up to HD (1280 x 720) via Pixel-Shift Technology
Maximum Brightness	250 Lumens (ANSI)
Aspect Ratio	16:9 4:3
Dynamic Contrast Ratio	100,000:1

## Lens

---

Focus	Manual
Optical Zoom	<i>None</i>
Throw Distance	32.6 - 130.7" / 82.804 - 331.978 cm
Projection Size	25 - 100" / 63.50 - 254.00 cm

## Features

---

Keystone Correction	Auto-Vertical:
Supported HDR Input Formats	<i>None</i>
Ceiling Mountable	Yes

---

Rear Screen Projection	Yes
------------------------	-----

---

Built-In Speaker	Yes (Mono)
------------------	------------

---

Speaker Power	1W
---------------	----

---

## Input/Output Connectors

---

Inputs/Outputs	<b>1 x</b> HDMI (HDMI Type-A) Audio, Video Input <b>1 x</b> USB 2.0 (USB Type-A) Data Input <b>1 x</b> 1/8" / 3.5 mm Mini Headphone Output
----------------	--

---

## Hardware

---

Wireless LAN / Wi-Fi	Yes, Built-in
----------------------	---------------

---

## General

---

Light Source	LED
--------------	-----

---

Expected Lamp Life	Low Brightness: 30,000 Hours
--------------------	------------------------------

---

Fan Noise	Full Brightness: 30 dB Medium Brightness: 28 dB Low Brightness: 25 dB
-----------	---

---

Security	Cable Lock Slot
----------	-----------------

---

Supported Audio File Types	AAC, AC3, CDDA, HE-AAC, LPCM, MP3
----------------------------	-----------------------------------

---

Supported Photo File Types	BMP, JPEG, PNG
Supported Video File Types	ASF, AVI, H.264/AVC, M2TS, M4V, MKV, MOV, MP4, MPEG, MPEG2, MPG, TP, TRP, TS, VC-1, VOB, WMV
AC Input Power	100 to 240 VAC, 50 / 60 Hz
Power Consumption	Full Brightness: 42 W Standby Mode (Lamp Off): < 0.5 W
Operating Temperature	32 to 104°F / 0 to 40°C
Storage Temperature	-4 to 140°F / -20 to 60°C
Operating Humidity	0 to 80%
Storage Humidity	0 to 80%
Dimensions (W x H x D)	5.1 x 1.5 x 5.1" / 13.0 x 3.8 x 13.0 cm
Weight	1.1 lb / 0.5 kg