

Projection System DLP

Display

Brightness (ANSI lumens) 3500

Native Resolution WXGA (1280x800)

Native Aspect Ratio 16:10

Contrast Ratio (FOFO) 10,000:1

Display Color 30-bit (1.07 billion colors)

Light Source Lamp

Light Source Life a. Normal 5000 hrs ,b. ECO 8000 hrs ,c. SmartEco 10000 hrs ,d. LampSave 12000 hrs

Optical

Throw Ratio 0.35

Zoom Ratio Fixed

Lens F/# = 2.5, f = 5.1 mm

Projection Offset (Full-Height) 122%

Keystone Adjustment 2D, Vertical ± 15 degrees; Horizontal ± 15 degrees

Lens Shift Vertical Vertical: $\pm 2\%$

Compatibility

Input Lag TBD

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB=Reduced blanking
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23~120Hz

I/O Interface

PC in (D-sub 15pin)	(x1) ,PC in-1 (shared with component video)
Monitor out (D-sub 15pin)	(x1)
Composite Video in (RCA)	(x1)
HDMI in	(x2) ,HDMI-1 (2.0a/HDCP2.2) ,HDMI-2 (2.0a/HDCP2.2)
LAN (RJ45)	(x1)
USB Type A	(x1) ,USB Type A-1 (2.0/Power Supply1.5A)
USB Type B	(x1) ,USB Type B-1(service)
USB Type Mini B	(x1) ,USB Type Mini B-1(PointWrite)
RS232 in (DB-9pin)	(x1)

Audio

Speaker	(x2) ,10W
Audio in (3.5mm Mini Jack)	(x1) ,1
Audio out (3.5mm Mini Jack)	(x1) ,1

Environment

-	AC 100 to 240 V, 50/60
---	------------------------

Power Supply	Hz
Typical Power Consumption (110V)	320W
Stand-by Power Consumption	<0.5W
Network Stand-by Power Consumption	<2W
Acoustic Noise (Typ./Eco.)(dB)	34/29
Operating Temperature 0~40°C	

Accessories

Remote Control w/ Battery	RCS011
Power Cord (by region) x1 (3.0M)	
VGA(D-sub 15pin) Cable	(Standard) ,1 (1.8m)
3D Glasses	(Optional) ,DGD5
Quick Start Guide	1 (18L)
Warranty Card (by region)	Yes
Wall Mount	(Standard) ,Yes, WM04G4

Dimension & Weight

Dimensions (WxHxD) (mm)	287.5x 206.9 x 373.3
Net Weight (kg)	5