EB-Z9900W

DATASHEET





The white EB-Z9900W large venue projector is simple to set up and features 3LCD technology, WXGA resolution and 9,200 lumens brightness.

The flexible EB-Z9900W is an impressive and versatile installation projector. This white model benefits from 9,200 lumens brightness and WXGA resolution. Able to project portrait aspect images for digital signage, the EB-Z9900W has a flexible installation angle, lens shift for off-centre positioning and plenty of calibration options, with optional Wi-Fi and HDBaseT connectivity.

Clear images and 3LCD technology

At 9,200 lumens the EB-Z9900W is an ultra-bright WXGA resolution projector. This projector benefits from Epson's 3LCD technology, which ensures highquality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than competitive projectors¹.

Perfect for large venues

Museums, auditoriums and corporate environments can benefit from the EB-Z9900W's large projected image, ideal for making a big impact.

Portrait projection

Able to project portrait aspect images, the EB-Z9900W is ideal for digital signage. Welcome to a whole new way of seeing things; portrait mode is also useful when a venue or event, such a fashion show, doesn't lend itself to landscape projection.

Easy set-up

As well as a flexible installation angle and lens shift for off-centre positioning, the EB-Z9900W includes plenty of calibration options such as edge blending, test patterns and Epson's Super Resolution feature.

Connectivity

The EB-Z9900W includes HDBaseT, which allows up to five connections in one. Optional Wi-Fi is also included for extra flexibility.

Short-throw capability

Great news for auditoriums and lecture theatres; a new and exclusive LU02 short throw lens allows this projector to be positioned closer to the screen.

KEY FEATURES

• High-brightness 9,200 lumens brightness

- Flexible
- Choose different installation angles • 3LCD technology
- For vivid colours and bright images
- Connectivity
- HDBaseT and optional Wi-Fi connectivity
- Portrait projection
 - When landscape isn't suitable





PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	1.03 inch with C2 Fine
IMAGE	
Colour Light Output	9,200 lumen-7,100 lumen (economy)
White Light Output	9,200 lumen - 7,100 lumen (economy)
Portrait Colour Light Output	8,100 lm
Portrait White Light Output	8,100 lm
Resolution	WXGA, 1280 x 800, 16:10
Contrast Ratio	15,000 : 1
Lamp	380 W, 2,500 h durability, 4,000 h durability (economy mode)
Lamp (portrait mode)	304 W, 1,000 Hours Durability
OPTICAL	
Projection Ratio	1.57 - 2.56:1
Zoom	Motorized, Factor: 1 - 1.61
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %
Projection Size	60 inches - 500 inches
Projection Lens F Number	1.65 - 2.51
Focal Distance	36 mm - 57.5 mm
Focus	Motorized
CONNECTIVITY	
Interfaces	USB 1.1 Type A, USB 2.0 Type B (Service Only), RS-232C, WLAN, Wireless LAN IEEE
	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in
	(6x), S-Video in, HDBaseT
GENERAL	
Energy Use	948 W, 788 W (economy), 0.37 W (standby)
Supply Voltage	AC 100 V - 240 V,50 Hz - 60 Hz
Product dimensions	741 x 534 x 197 mm (Width x Depth x Height)
Product weight	26 kg
Noise Level	Normal: 39 dB (A) - Economy: 35 dB (A)
Temperature	Storage -10° C - 60° C
Humidity	Operation 20% - 80%, Storage 10% - 90%
OTHER	
Warranty	36 months Carry in or 20,000 h, Lamp: 12 months or 1,000 h
	Optional warranty extension available

LOGISTICS INFORMATION

ѕки	V11H609040
EAN code	8715946541266
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	4 Units
Pallet Size Block	4 Units

EB-Z9900W

WHAT'S IN THE BOX

- Computer cable
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries
- User's Manual Set

OPTIONAL ACCESSORIES

- Lamp (x2) ELPLP82
- V13H010L82
- Lamp ELPLP81
 V13H010L81
- 3D Polarizer ELPPL01
 V12H618A01
- Wireless LAN Adapter (b/g/n) ELPAP07 V12H418P13
- Ceiling Mount (Low) ELPMB25 V12H003B25
- Ceiling Mount (High) ELPMB26 V12H003B26
- HDBaseT Transmitter ELPHD01 V12H547041
- 3D Glasses (Passive for Child, x5) ELPGS02B V12H541B10
- Quick Wireless Connect USB key ELPAP09 V12H005M09

OPTIONAL LENSES

- Lens (ST Off Axis) ELPLU02 V12H004U02
- Lens (Long Throw) ELPLL07 V12H004L07
- Lens (Middle Throw 1) ELPLM06 V12H004M06
- Lens (Middle Throw 2) ELPLM07 V12H004M07
- Lens (Rear Wide) ELPLR04 V12H004R04
- Lens (Wide) ELPLW04
 V12H004W04

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Web: www.epson.co.uk www.epson.ie 1. Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO



Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.