
<section-header>

DATASHEET



This WUXGA LCD laser projector offers superior images and a long-lasting, low maintenance performance

Promising long-life laser projection for large venues, this 7,000 lumens WUXGA projector delivers rich, vivid colours thanks to Epson's 3LCD technology and equally high White and Colour Light Output. With flexible installation and low maintenance, this 4K enhanced projector offers a fit-and-forget solution for scenarios in which only superior projections will do.

Laser-sharp images

Ensure superb quality and the best possible delivery of presentations with this laser installation projector for large venues. Featuring 3LCD technology and equally high White and Colour Light Output, its WUXGA resolution images are vivid and bright, even in daylight. Including a newly developed inorganic phosphor wheel, the projector offers superior light and heat resistance to deliver excellent reliability. For a next-level viewing experience, the projector features 4K enhancement, giving images exceptional sharpness and clarity that lasts for up to 56,000 hours¹ thanks to a long laser life. A built-in camera is also included to ensure accurate image calibration.

Flexible positioning

Thanks to a new range of motorised lenses, including optional ultra-short throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image.



KEY FEATURES

- Laser light source technology Reliable and long-lasting picture quality (up to 56,000 hours²)
- Superior picture quality Enhanced light output; superior white balance; better colour matching
- HD images with 4K enhancement Exceptional sharpness, clarity and detail for the real 4K effect
- Flexible 360° installation True flexibility without distortion or loss of brightness
- Added peace of mind Product comes with 5-year, 20,000 hour warranty





PRODUCT SPECIFICATIONS

3LCD Technology
0.76 inch with C2 Fine
7,000 lumen- 4,900 lumen (economy) In accordance with IDMS15.4
7,000 lumen - 4,900 lumen (economy) In accordance with ISO 21118:2012
WUXGA, 1920 x 1200, 16:10
4K enhancement
16:10
2,500,000 : 1
2,000 : 1
20,000 Hours Durability High, 30,000 Hours Durability Eco
7,000 lm
7,000 lm
Manual vertical: ± 45 °, Manual horizontal ± 30 °
Upto 1.07 billion colours
1.44 - 2.32:1
Motorized, Factor: 1 - 1.6
Motorized - Vertical ± 67 %, horizontal ± 30 %
10 positions
50 inches - 300 inches
1.7 - 2.3
24.02 mm - 38.24 mm
Motorized
1.5 m - 9.4 m
1.5 m - 9.4 m
1.5 m - 9.4 m 2.5 m - 15.1 m
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in,
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only)
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo,
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 384 W
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 384 W AC 100 V - 240 V, 50 Hz - 60 Hz
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 384 W AC 100 V - 240 V, 50 Hz - 60 Hz 566 x 492 x 211 mm (Width x Depth x Height)
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 384 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 21 kg
 1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 384 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 21 kg Normal: 34 dB (A) - Economy: 28 dB (A) - Eco2: 1 dB (A)
1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 384 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 21 kg
 1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 384 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 21 kg Normal: 34 dB (A) - Economy: 28 dB (A) - Eco2: 1 dB (A) White
 1.5 m - 9.4 m 2.5 m - 15.1 m le 1.53 m - 15.1 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only) Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Built-in speaker, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 566 W, 384 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 384 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 21 kg Normal: 34 dB (A) - Economy: 28 dB (A) - Eco2: 1 dB (A) White

EB-L1200U

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- VGA cable
- Cable cover
- CD Manual



OPTIONAL ACCESSORIES

- Air Filter ELPAF51 EB-L1000 series V13H134A51
- Ceiling Mount ELPMB47 Low EB-G7000/L1000 V12H802010
- Ceiling Mount ELPMB48 High EB-G7000/L1000 V12H803010
- 3D Polarizer ELPPL01 V12H618A01
- Wireless LAN Adapter ELPAP10 V12H731P01
- HDBaseT Transmitter ELPHD01 V12H547041
- Quick Wireless Connect USB key ELPAP09 V12H005M09

OPTIONAL LENSES

- Lens ELPLM09 Mid throw 2 G7000/L1000 series V12H004M09
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLX01 UST lens G7000 series & L1100,1200,1300,1400/5U V12H004X01
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1 V12H004W05
- Lens ELPLM08 Mid throw 1 G7000/L1000 series V12H004M08
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B

LOGISTICS INFORMATION

ѕки	V11H734040
EAN code	8715946616766
Country of Origin	China

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Web: www.epson.co.uk www.epson.ie

1. - Laser life of up to 56,000h hours in custom mode



EB-L1200U