



Epson MeetingMate EB-1410Wi

MeetingMate – The ultimate meeting solution in one simple device with high brightness!

PC Free Whiteboard function – Perfect alternative to copyboards and conventional whiteboards, this function facilitates productive meetings and enhances collaboration – without the need for a PC! After the meeting, you can save, print or email the meeting notes instantly.

Split screen function – Project data and video simultaneously.

Remote projection and interactive collaboration – Share content and collaborate from multiple remote locations

Dual Pen Interactivity – Two users can annotate over content at the same time.

Control pad – Neatly designed and easy to install for efficient and intuitive operation.

Epson MeetingMate EB-1410Wi



Product Specifications

PRODUCT NAME	Epson EB-1410Wi
PRODUCT CODE	V11H480053
TECHNOLOGY	
Projection Technology	Epson 3LCD, 3-chip technology
Projection System	RGB liquid crystal shutter projection system
LCD Panel	0.59-inch with MLA
OPTICAL	
Zoom	1.0-1.35 (Digital Zoom)
Screen Size	60" to 100" [0.348 to 0.597m]
Projection Distance	74.3" screen 0.438 m
Throw Ratio	0.27 (Zoom:Wide) / 0.37 (Zoom:Tele)
Projection Lens Type	No Optical Zoom / Focus (Manual)
Projection Lens F Number	1.80
Projection Lens Focal Length	3.71mm
Focus Method	Manual focus
Offset	6:-1
IMAGE	
Colour Light Output	3100 lumens
White Light Output	3100 lumens
Resolution	WXGA
Native Aspect Ratio	16:10
Contrast Ratio	3000:1
Keystone Correction	Vertical: -3 to +3 degrees Horizontal: -3 to +3 degrees
CONNECTIVITY	
Analog RGB Input:	Video - D-sub 15pin (Blue molding) x 1 Audio - Stereo mini jack x 1
Analog RGB Output:	Video - D-sub 15pin (Black molding) x 1 (Output signal : Computer 1 only) Audio - Stereo mini jack x 1
Video I/O	Video - Composite Video: RCA (Yellow) x 1 Video - Component Video: D-sub 15pin (Blue molding) x 1 (in common with Analog RGB connector) Video - RGB Video: D-sub 15pin (Blue molding) x 1 (in common with Analog RGB connector) Audio - Stereo mini jack x 1 (in common with Analog RGB Audio terminal)
Digital Input	HDMI x 1 (for Analog audio : Stereo mini jack x1) DisplayPort x 1
Control I/O	USB - USB Type B x 1 (for USB Display, mouse, K/B, Interactive) Serial - D-sub 9pin x 1 Remote Control Input - Stereo mini jack x 1
Memory I/O	USB Type A x 1 (for USB Memory) USB Type A x 1 (for Document Camera)
Network I/O	USB - Type A x 1 (Special I/O) Wired LAN - RJ45 x 1 (100Mbps)
Wireless connectivity	Included ELPAP07 Wireless LAN unit
Speaker Output	Monaural: 10 W x 1

ADVANCED FEATURES	
Split screen	Yes
EasyMP Network Projector control and projector management via network	Yes
EasyMP Network Projection	Yes
EasyMP Network Multi PC Projection	Yes
Windows Network Projector	Yes
Message Broadcasting	Yes
Search Access Point (Site Survey)	Yes
Network Firmware download	Yes
Quick Wireless Connection	Yes
USB Plug 'n Play	Yes
Instant Off	Yes
Direct Power On	Yes
Security	Kensington® - lock provision Padlock & Security cable hole Wireless LAN unit lock Password protect function (Power On, Network, Protection of User logo)
Colour Modes	Dynamic, Theatre
External control pad	Yes
EXTERNAL CONTROL PAD	
Dimensions (excl Protusion) WxHxD	136 x 149 x 29 mm
Weight	240 g (Excluding Batteries and Rubber feet)
Buttons	Power, Whiteboard, Source search, Capture, Save, Print
Control I/O	Upstream port - USB Type A x 1 (for USB Display, mouse, K/B, Interactive) Upstream port (Remote Control output) - Stereo mini Jack Downstream port - USB Type B x 1 (for USB Display, mouse, K/B, Interactive)
Memory I/O	Upstream port - USB Type B x 1 Downstream port - USB Type A x 2 (for USB flash storage, Printer)
GENERAL	
Dimensions (excl feet) WxHxD	367 x 155 x 375 mm
Weight	without SlidePlate: 5.6 kg / with SlidePlate: 6.3 kg
Lamp Warranty	1 Year (or 750 hours)*
Projector Warranty	3 yrs
Lamp Hours	3500 hours (Power consumption : Normal) 5000 hours (Power consumption: ECO)
Lamp Type	215 W UHE
Power Consumption: Lamp On	307W (Normal) / 222W (ECO)
Power Consumption: Standby	5.0W (Communication On) 0.27W (Communication Off)
Fan Noise Level	Brightness Control Normal: 35dB Brightness Control ECO: 28dB

* Whichever comes first. For more information visit www.epson.com.au/warranty

Better Products for a Better Future

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON AUSTRALIA
3 Talavera Road
North Ryde NSW 2113
Tel: (02) 8899 3666
www.epson.com.au

EPSON NEW ZEALAND
Level 2, 7-9 Fanshawe Street
Auckland, 1010
Tel: (09) 366 6855
www.epson.co.nz

ABN 91 002 625 783
02/13

EPSON
EXCEED YOUR VISION