

An ideal device for corporate or educational use, the EB-1930 is a great combination of quality output and features at an affordable price.

### Convenient use

The Epson EB-1930 combines high-quality output, value-added features and affordability, into a compact and portable projector. It is perfect for corporate or educational use, as it can be easily installed in meeting rooms or used portably from a desktop.

### High quality picture

Utilising Epson's 3LCD technology to ensure clearly projected images, the EB-1930 produces vivid, natural colours and an equally high White and Colour Light Output, even in daylight.

### Connectivity

The EB-1930 boasts a DisplayPort connector, allowing you to show high definition audio and video content with ease.

### Enhanced productivity

Productivity can be greatly increased with a range of features available with the EB-1930, such as Quick Corner.

## **KEY FEATURES**

- Ultra bright output 4,200 lumens White/Colour Light Output
- Picture quality 3LCD technology for vivid colours
- Clock / Schedule Program projector actions in advance
- PC free/Slide show Read PDFs directly from a USB stick





### **PRODUCT SPECIFICATIONS**

TECHNOLOGY Projection System	3LCD Technology, RGB liquid crystal shutter	WHAT'S
LCD Panel	0,63 inch with MLA (D7)	<ul> <li>Comput</li> </ul>
IMAGE Colour Light Output White Light Output Resolution Contrast Ratio Lamp Keystone Correction Colour Processing	4.200 lumen-2.730 lumen (economy) 4.200 lumen - 2.730 lumen (economy) XGA, 1024 x 768, 4:3 3.000 : 1 215 W, 3.500 h durability, 5.000 h durability (economy mode) Auto vertical: $\pm$ 30 °, Manual horizontal $\pm$ 30 ° 10 Bits	<ul> <li>Comparison</li> <li>Power of</li> <li>Softwar</li> <li>User material</li> <li>User material</li> <li>Remote</li> </ul>
OPTICAL		OPTION
Projection Ratio Zoom Projection Size Projection Distance Wide Projection Distance Tele Projection Lens F Number Focus Offset Projection Lens Zoom Ratio Lens CONNECTIVITY	1,38 - 2,24:1 Manual, Factor: 10 - 16 30 inches - 300 inches 0,8 m - 8,4 m (60 inch screen) 1,4 m - 13,9 m (60 inch screen) 1,51 - 1,99 18 mm - 29 mm Manual 8,6 : 1 1 - 1,6 : 1 Optical	<ul> <li>Air Filter - V13H134,</li> <li>Lamp - EL V13H0101</li> <li>Soft Carry V12H0011</li> <li>Ceiling Mc V12H0031</li> <li>Ceiling Pip V12H0031</li> <li>Ceiling Pip V12H0031</li> </ul>
USB Display Function Interfaces	3 in 1: Image / Mouse / Sound USB 2.0 Type B, USB 2.0 Type A, RS-232C, HDMI in, RGB out, Stereo mini jack audio out, RGB in (2x), Stereo mini jack audio in (2x), 10 Base-T, VGA in (2x), VGA out, Composite in, Display Port	V12110031
	Karainshan ladu. Sesuritu kar Osmlari senal ladu. Dessurard ladu	
Security Features	Kensington lock, Security bar, Control panel lock, Password lock AV Mute Slide, Automatic input selection, Automatic keystone correction, Direct Power on/off, Document Camera Compatible, Freeze image, Instant on/off, JPEG Viewer, Network administration, PC Free, Quick Corner, Slide show, Split-Screen-Function	
Video Colour Modes	Blackboard, Dynamic, Photo, Presentation, sRGB, Theatre, Whiteboard, DICOM SIM	
2D Colour Modes	Dynamic	
GENERAL		
Energy Use	298 W, 212 W (economy), 0,44 W (standby)	
OTHER Warranty	36 months Carry in or 8.000 h, Lamp: 12 months or 1.000 h	

## LOGISTICS INFORMATION

SKU	V11H506040
EAN code	8715946512563
Dimensions Single Carton	517 x 342 x 196 mm
Carton Weight	5,51 Kg
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	40 Units



### Epson EB-1930

#### S IN THE BOX

- uter cable
- cable
- are (CD)
- nanual
- nanual (CD)
- te control incl. batteries

# NAL ACCESSORIES

- ELPAF41
- 4A41 ELPLP74
- 0L74
- ry Case ELPKS65 1K65
- Nount (White) ELPMB23 3B23
- Pipe (450mm) ELPFP13 3P13
- Pipe (700mm) ELPFP14 3P14

