

SPECIFICATIONS

SPECIFICATION

Projection System: 0.55" SVGA
Native Resolution: 800x600
DC Type: DC3
Brightness: 3600
Contrast Ratio with SuperEco Mode: 22000:1
Display Colour: 1.07 Billion Colours
Light Source: Lamp
Light Source Life: 5000/15000
Lamp Watt: 190W
Lens: F=2.56-2.68, f=22-24.1 mm
Projection Offset: 120%+/-5%
Throw Ratio: 1.96-2.15
Image Size: 30" - 300"
Throw Distance: 1.19m-13.11m(100" @3.98m)
Keystone: +/- 40° (Vertical)
Optical Zoom: 1.1x
Digital Zoom: 0.8x ~ 2.0x
Audible Noise (Normal/Eco): 31 / 27dB
Resolution Support: VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility: NTSC, PAL, SECAM
Horizontal Frequency: 15K~102KHz
Vertical Scan Rate: 23~120Hz

INPUT

Computer in (share with component): 2
Composite: 1
Audio-in (3.5mm): 1
HDMI (HDCP): 2 (HDMI 1.4/ HDCP 1.4)

OUTPUT

Monitor out: 1
Audio out (3.5mm): 1
Speaker: 2W
USB Type A (Power): 1 (5V/1.5A)

CONTROL

RS232: 1
USB Type Mini B (Services): 1

OTHERS

Power Supply Voltage: 100-240V+/- 10%, 50/60Hz AC
Power Consumption: Normal: 260W / Standby: <0.5W
Operating Temperature: 0~40°C
Net Weight: 2.2kg
Dimensions (WxDxH) with Adjustment Foot: 294x218x110mm
Language: English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord: 1
VGA Cable: 1

Remote Control: 1
QSG: 1

OPTIONAL ACCESSORY

Lamp/Light Source: RLC-108
Carry Bag: PJ-CASE-008
