

SPECIFICATIONS

CONNECTIVITY

Transmitter: HDMI in x1 / HDBT x1 (LAN) / IR receiver x1(3.5mm) IR Blaster x1 (3.5mm) / Power socket x1 (with lock)

Receiver: HDMI out x1 / HDBT x1 (LAN) / IR receiver x1(3.5mm) IR Blaster x1 (3.5mm) / Power socket x1 (by Micro USB)

COMPATIBILITY

Support Output Resolution

(by Cat 5e/6/6a/7): HDMI: 1080P up to 70m

HDMI: 4K/2k@30 up to 40m

HDCP / CEC compliant

POWER

Transmitter: 100~240VAC @ 50/60Hz, 12V/1A output (power adaptor)

Power consumption: 3W (Maximum)

Receive: from Transmitter or USB power (5V/1.5A)

Power consumption: 7W (Maximum)

OPERATING CONDITION

Temperature: 23°F to 104°F (-5°C to 40°C)

Humidity: 0% to 95% Non-Condensing

Altitude: 0 to + 13123 ft

STORAGE CONDITION

Temperature: -22°F to 140°F (-30°C to +60°C)

Humidity: 0% to 95% Non-Condensing

DIMENSIONS

Transmitter Physical: 99.5 mm (W) x 74mm (D) x 18 mm (H) / 3.92" (W) x 2.91" (D) x 0.71" (H)

Receiver Physical: 41.5 mm (W) x 84.5 mm (D) x 23.9 mm (H) / 1.63" (W) x 3.33" (D) x 0.94" (H)

Packing Carton Box : 264 mm (W) x 170 mm (D) x 77 mm (H) / 10.39" (W) x 6.69" (D) x 3.03" (H)

Shipping carton: 420mm (W)x 358(D)x 291mm(H)/ 16.54" x 14.10" x 11.46"

WEIGHT

Gift box : Net: 214g (0.47lb) (Transmitter: 122g, Receiver 92g)

Gross: 650g(1.43lb)

Shipping carton : Gross: 7.5kg (16.54lb)

REGULATIONS

Safety/EMC: FCC, CE, ErP, RoHS

INCLUDE ACCESSORIES

The Top Level Assembly shall consist of : HB10B Transmitter /HB10 Receiver/ Universal Power Adapter x 1 (with US, EU, UK head) / Quick Start Guide / IR receiver x1 / IR blaster x1 /Wall mount with screws x3 (2 for Receiver, 1 for receiver)
